Centroid Products DETAILED ORDER FORM 7/26/13

website: centroidproducts.com email: info@centroidproducts.com fax: 386-423-3709 tel: -3574

PART 1: CUSTOMER INFORMATION

- --We ship by <u>UPS only</u>, and only using our own UPS account number.
- --We don't ship outside the US. You could give us a US shipping address. Or email mari@centroidproducts.com to find a reseller to buy through who doesnt mind shipping outside the US.
- --We don't ship to Florida except for resale (tax cert must be faxed). Florida individuals--use Lauderdale Speedometer (800-951-5123)
- --A typical shipping charge for <u>one sender under 38"</u> by <u>ground</u> in the <u>lower 48 states</u> is \$9. Next Day shipping is \$30 at the very least. If you are sensitive to shipping price, <u>or before sending a check</u>, please <u>call</u> for the shipping price. Assume it will take us at least a week to ship.
- --We are only set up for Visa or Mastercard.

| SHIP TO: | phone | email: | |
|-------------|-------------------------------|---|--|
| Company8 | kattention, or person's name: | · | |
| Street (no | PO boxes; also, must include | e "street" or "road", etc, not just "12 | 23 Maple") |
| | | | |
| City, State | , Zip | | Does anyone live at this address? (UPS question) |
| Visa/MC# | I | _ | exp |
| Name on o | card incl any initial | | 3-digit security code from back of card |
| Ground sh | ipping ok? | (ex: 1 day to Florida, 3 to Missour | i, 5 to California). Or 3day, 2day, or \$1day\$ |

PART 2: ORDER FORMS

See the detailed instructions, below. <u>If you don't want to be stuck with the wrong sender, please don't guess or leave empty blanks.</u> The example shown is what your entries should look like. Or order by phone through Mary at 386-423-3574 between 8a-2p EST (early best!) Mon/THU-- she'll walk you through the questions.

SENDERS:

| Ln | Liq | Len | A/ S | Bat | Output/ | for gauge | Mount | Options | =Price | x Qty | Total |
|-----|-----|---------------|---------|-----|--------------------|-----------|------------------|--------------------------|---------|----------|-------|
| Α | | | | | | | | | | | |
| В | | | | | | | | | | | |
| С | | | | | | | | | | | |
| D | | | | | | | | | | | |
| Е | | | | | | | | | | | |
| F | | | | | | | | | | | |
| ex. | GAS | 13.5" \$59 | Α | 12V | 240/33 3 VDO 30 | | 1/2" FL. \$15 | LOW=12.5%, W \$8, \$3 | /S \$85 | 1 | \$xxx |

PART 3: DETAILED INSTRUCTIONS 3A) SENDERS

Liq: gas (but not E85--it conducts too well), dsl (onroad), olddsl (offroad/boats), wtr(potable only; we no longer make black/graywater senders)

Len: For straight probe, 5 hole mount: top surface to 1/2" or more off the bottom. For flatted/hex threaded mount: top of tank's threaded fitting to bottom of tank or higher (fitting provides natural 1/2" offset). For bent 5 hole mount (sidemount; no threaded sidemounts): distance from bend to bottom of probe, given 2" from top of tank to opening, to accomodate flange, and at least 1/2" clearance at bottom (the distance from the opening to the bend will be approximately 3"). In all cases: if waterscreen is ordered for fuel probe, your length includes 1/2" of non-sensing screen.

Pricing for gauge senders: 3 to 6"=\$60 fuel\(^{\$}\$62 water, 6+ to 12"=\$62/64, 12+ to 24"=\$64/66, 24+ to 36"=\$71, 36+ to 48"=\$79, 48+ to 72"=\$89, 72+ to 92"=\$150

A/S: For FUEL probes with 5-hole mount: we can use **quarter inch tubing (code A)** instead of half inch if the probe is 24" or less and either your tank opening is less than 1" diameter or you order a customer-bendable sender. For all probes: we prefer you order the needed length. However if you may need to **shorten the sender, show code S**. Inch lengths in the following ranges can be shortened to the bottom of that range: 3 to 6, 6+ to 12, 12+ to 24, 24+ to 48, 48+ to 96, 96+ to 192.

Bat: Supply voltage for sender; <u>12V</u>, <u>24V</u>, <u>or 32V</u>. Other than our 240/33 2-terminal sender, all our senders require a battery-voltage connection in addition to the normal Send and Negative connections of a float sender.

Output/ for gauge: We make the following outputs to match your gauge: 240/33 ohms, 0/90 ohms, 10/180 ohms, 76/6 ohms, 100/6 ohms, 0/30 ohms, 0/5 volts (eg ISIS), 0/4V (eg for CompuTank displays), 4/20 milliamps. With our new programmable senders, we can do ranges we havent done before if we email you a form so you can make a few measurements for us. When specifying your output range, please also indicate the *brand and part number of your gauge* if possible so we can see if your listed output seems correct.

Dont have a gauge? Try Livorsi (847-548-5900), whose fuel and water gauges work with our 240/33 ohm 2-term senders.

Two-terminal for 240/33 ohms: we can make a 2-terminal sender (no battery connection needed) for 240/33 ohm gauges by the following manufacturers only: Stewart Warner, Teleflex, Datcon, Livorsi (formerly Gaffrig), US Gauge, OMC. Please indicate 240/33-2T for the 2-terminal sender if your 240/33 gauge is by one of the listed manufacturers. The 3-terminal 240/33 will work with any 240/33 ohm sender, except we make a special sender for the Westberg 240/33. Detectors, controllers: we no longer make these alarm-only devices. If all you need is an alarm(s), choose the 0/5V output with the optional alarm output (see below).

Mount: Our standard mount is $\underline{5\text{-hole}}$, the SAE bolt pattern, with a nylon holder. We also have three NPT-threaded aluminum holders: $\underline{3/8"}$ flatted, $\underline{1.5"}$ flatted (and for the 0/5V or 0/4V outputs, or detect/high or detect/low *only*, we have $\underline{1/2"}$ hex). We no longer use the method of epoxing bushings to the bottom of our nylon holders. The flatted holders can be wrenched with a 2-5/8" wrench opening; the hex with a 1-5/8". Subtract 1/4" from your thread measurement to get its NPT size (eg 3/4" across threads is called 1/2" NPT). We dont do the 3/4" NPT, 1" NPT, or 1.25" NPT sizes and longer. **Pricing by mount**: 5 hole=\$0, flatted=\$15, hex=\$15

Options:

Fuel water-screens: Water in a fuel tank will bridge between our fuel sender's inner and outer tubes and cause an Empty reading. If you dont want this warning you can buy a water screen. Specify: WS. **Price**: \$4

Factory bends: Specify <u>BEND XXdeg/YY oclock</u>, where xx is the angle *from straight * (90deg max, single bend). YY is 8:00 if you will drill to match our sender, or is read from our faxed template if you have existing mounting holes. **Price=** \$2

Customer bendable: For FUEL tanks 24" or less, we can make the sender with quarter inch tubing, bendable by the customer. Specify <u>BENDABLE XX"</u>, where xx is the inches from head to the intended bend (1/4 of the probe max). The water probes can be bent by the customer easily by heating the tubing. **Price=** \$2

Low/high alarms: Our new programmable senders have a shared alarm terminal which can do low-alarm-only, high-alarm-only, low and high, low-on/high off, or high-on/low off. (Notes: 0/5V in hex holder, and 4/20ma, cant have alarms). Specify what alarm(s) you need, if any, <u>such as LO=10%</u>, HI=95%. **Price=** \$8.

Tank shape correction(lcm): Programming can be added to the sender to correct for odd-shaped tanks. The programming is designed from your inch/gal tank chart (\$60) or your dimensioned tank drawing (\$120). Specify <u>LCM/DWG</u> or <u>LCM/CHART</u>. **Price**= one-time design charge of \$60 or \$120.

Damping: Some customers with unbaffled tanks need our electronic damping to keep the reading from bouncing due to tank slosh. This is only true for long, shallow tanks, however, such as the 6-foot tanks in motorhomes. Most users *dont* need damping. Damping only removes short-term changes, not a long-term tilt. Specify DAMPED. **Price**= \$0.

Isolated ground for fuel: some boat customers request that the tubing of our fuel sender be direct-current-isolated from the Negative terminal of the sender for corrosion reasons (our water senders and 4/20mA senders are isolated by default). Specify: ISOL. **Price**= \$0